

Intended Use

- To fill fine cracks and open joints of 1-3 mm depth.
- Suitable for untreated or primed veneer and solid woods, laminate, MDF, metal.
- Recommended for indoor use. – If used outdoors, recoating is necessary.

Characteristics

- A coloured, creamy one-component filler paste.
- All colours can be intermixed.
- Drying period: approx. 30-60 minutes.
- Heat-resistant up to 100°C.

Application Notes

If the correct colour shade is not available among the 10 standards, apply several colours on the Mixing Palette and mix the desired shade with the Working Spatula. Apply AQUA Wood Filler of the relevant colour to the damaged area (suitable for filling depths of 1-3 mm).

Important: Proceed in two steps.

1st step: Firmly press in the filler paste.

2nd step: Slightly overfill the damaged area.

When cured (curing time: approx. 30-60 minutes – with a hair drier approx. 5-10 minutes), remove excess material with the Metal Planer and sand over with 180-240 grit Dry Sandpaper. With delicate surfaces (closed-porous), re-sand with 1,800-12,000 grit Micro Sanding Paper (very fine). Apply Special Repair Lacquer PLUS to protect the repaired area from dust and dirt (spray distance approx. 30-40 cm). AQUA Wood Filler can be varnished with all König lacquers.

Note: Applying a sufficient coat of Furniture Lacquer PLUS even lends weather-resistance to the repaired area (create coat thickness!).

Physical Properties and Shelf Life

- Resistance:** up to 100°C
Mechanical stability: good
Curing time: 30-60 minutes for 1-3 mm thick layers – approx. 5-10 minutes when using a hair drier
- Substrate:** untreated/primed veneer and solid wood, laminate, MDF, metal
Overcoatable: with all König lacquers
Adhesion: good up to very good on all substrates mentioned above
Shelf life: minimum 1 year (stored at room temperature, in unopened original container)

Protect from frost!

Safety Precautions

- The mixture is classified as not hazardous according to regulation (EC) No. 1272/2008 [CLP].

Disposal

- Dispose of containers with the normal household waste only when completely empty or dried out.
- Leftover material to be disposed of in accordance with EWC 080112 (waste paint and varnish other than those mentioned in 080111).

Packaging

On request.

*Further information on the internet at
www.heinrich-koenig.de*

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).



Seit 1892

Heinrich König & Co. KG

An der Rosenhelle 5 • D-61138 Niederdorfelden

Phone: 0 61 01-53 60 0 • Fax: 0 61 01-53 60 11

E-mail: info@heinrich-koenig.de

Issue 20/17